according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ZACKIVATOR

UFI: 82WT-R9DT-U00Q-Q3C6

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

MUTIPLEX Modellsport GmbH & Co. KG Westliche Gewerbestr. 1 D-75015 Bretten

www.multiplex-rc.de



1.4. Emergency telephone

<u>number:</u>

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetone; propan-2-one; propanone **Signal word:** Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 Store locked up.

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 2 of 11

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. Vapours can form explosive mixtures with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation	(EC) No 1272/2008)	•		
115-10-6	dimethyl ether			50 - < 70 %	
	204-065-8	603-019-00-8	01-2119472128-37		
	Flam. Gas 1, Compressed gas; H220 H280				
67-64-1	acetone; propan-2-one; propanone				
	200-662-2	606-001-00-8	01-2119471330-49		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				
99-97-8	N,N-dimethyl-p-toluidine				
	202-805-4	612-056-00-9	01-2119937766-23		
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H331 H311 H301 H373 H412				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	-
67-64-1	200-662-2	acetone; propan-2-one; propanone	30 - 40 %
	inhalation: LC	ation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7400 mg/kg; oral: LD50 = 5800 mg/kg	
99-97-8	202-805-4	805-4 N,N-dimethyl-p-toluidine	
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 3 of 11

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Dyspnoea

Headache

Dizziness

Dizziness

Nausea

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO2))

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 4 of 11

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use personal protection equipment.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

7.3. Specific end use(s)

Adhesion promotor (@0102.B010607)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
115-10-6	Dimethylether	1000	1920		TWA (8 h)	

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 5 of 11

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
67-64-1	7-64-1 acetone; propan-2-one; propanone			
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³

PNEC values

CAS No	Name of agent		
Environmental compartment Value		Value	
67-64-1	7-64-1 acetone; propan-2-one; propanone		
Freshwater 10,6 mg/l		10,6 mg/l	
Marine water 1,06		1,06 mg/l	
Freshwater sediment 30,4 m		30,4 mg/kg	
Marine sediment		3,04 mg/kg	
Micro-organisms in sewage treatment plants (STP)		100 mg/l	
Soil 29,5 m		29,5 mg/kg	

8.2. Exposure controls









Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

Suitable material: Butyl caoutchouc (butyl rubber) Thickness of the glove material >= 0,5 mm

Permeation time (maximum wear duration): > 60 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. (EN 340)

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 6 of 11

Respiratory protection necessary at: high concentrations, exceeding exposure limit values

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid (Aerosol)
Colour: colourless
Odour: like: Acetone
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not applicable
not determined

boiling range:

Extremely flammable aerosol. Flammability: Lower explosion limits: not determined Upper explosion limits: not determined Flash point: not applicable Auto-ignition temperature: not determined Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: partially soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density:

Relative vapour density:

Particle characteristics:

not determined

0,703 g/cm³

not determined

not determined

not determined

not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Pressurised container: May burst if heated.

Further InformationNo information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air. Pressurised container: May burst if heated.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

No information available.

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 7 of 11

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 21152,6 mg/kg; ATE (dermal) 63457,9 mg/kg; ATE (inhalation vapour) 634,58 mg/l; ATE (inhalation dust/mist) 105,763 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
67-64-1	acetone; propan-2-one;	acetone; propan-2-one; propanone						
	oral	LD50 mg/kg	5800	Rat	Manufacturer			
	dermal	LD50 mg/kg	7400	Rabbit	Manufacturer			
	inhalation (4 h) vapour	LC50	76 mg/l	Rat	Manufacturer			
99-97-8	N,N-dimethyl-p-toluidine							
	oral	ATE	100 mg/kg					
	dermal	ATE	300 mg/kg					
	inhalation vapour	ATE	3 mg/l					
	inhalation dust/mist	ATE	0,5 mg/l					

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 8 of 11

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
67-64-1	acetone; propan-2-one; propanone	
99-97-8	N,N-dimethyl-p-toluidine	2,81

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 9 of 11

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63 190 277 327 344 381 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 10 of 11

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Extremely flammable aerosol. Pressurized container: May burst if heated.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 99,8 % (702 g/l)

Information according to 2012/18/EU

(SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information

Aerosol Directive (75/324/).

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under

the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

according to Regulation (EC) No 1907/2006

ZACKIVATOR

Revision date: 30.06.2023 Product code: MAC.A9.Y150 Page 11 of 11

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

	•
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)